



# Wireless Pan Tilt Zoom Video Baby Monitor

## SEW-3041

VGA Resolution Camera and 4.3" Portable Monitor Package

### Monitor (Parent Unit) Features

- 4.3" Large display screen monitor unit
- Battery level indicator
- Sleep mode to extend battery life
- Integrated flip stand and belt clip
- Quiet mode to remove white background noise
- Two-way talk button

### Camera (Baby Unit) Features

- Elegant compact design
- High resolution camera
- Non-visible IR LEDs for safe night time monitoring
- Built-in mic and speaker for two-way talk



**Pan, Tilt & Zoom**  
Monitor your baby's room from any angle



**Interference-free**  
Long range signal allows monitoring up to 900ft



**Night Vision**  
See your baby in the dark



**Two-way Talk**  
Hear and talk to your baby



**Remote Night Light**  
Soothe your little one to sleep



## SEW-3041W

**SYSTEM GENERAL**

Operating Frequency Range	2400MHz ~ 2483.5MHz
Transmitting Power	Max. 17dBm
Monitor Sensitivity	-88dBm
Type of Spread Spectrum TX	FHSS
Type of Modulation	GFSK
Data Rate	3Mbps
Transmission range	Outdoor 300m (Eye of sight), Same as SEW-3036
Weight	942g (2.08 lb)

**WIRELESS CAMERA**

Image Sensor Type	1/5" Color CMOS Image Sensor
Effective Pixel	H : 640 / V : 480
Resolution	640 x 480
Image Compression	MJPEG
White Balance	Auto
Lens	EFL=3.0mm, F=2.5
Viewing Angle (Diagonal)	57
IR LED Type / Night Vision	8pcs IR LED – 940nm /5m
Loud Speaker Output	80dBA
Power Requirement	6V DC ±10%
Power Consumption	480mA condition night vision mode, Motor in motion and talk back
VOX Level Detection	High : 50dBA / Low : 60dBA
Operating Temperature Range	0°C ~ +40°C (+32°F ~ +104°F)
Operating Humidity Range	85% RH
Environment Rating	Indoor use only
Pan Angle	300°
Tilt Angle	110°
Regulation Compliance	FCC / CE
RoHS Compliance	Yes for CE version only
Audio	Built in Microphone / Speaker
Weight	214g (0.47 lb)

**WIRELESS MONITOR**

Display Type / Size	Color TFT 4.3"
Resolution	480 x 272
Viewing Angle	H : 80 degree, V : 100 degree
Number of Camera Support	Up to 4 cameras
Power Requirement	Adapter : DC 6V ±10%, Battery : 3.7V Li-polymer
Loud Speaker Output	80dBA
Power Consumption	480mA maximum condition charging + Speaker with voice at volume 5
Operating Temperature Range	0°C ~ +40°C (+32°F ~ +104°F)
Operating Humidity Range	85% RH
Environment Rating	Indoor use only
Regulation Compliance	FCC / CE
RoHS Compliance	Yes for CE version only
Audio	Built in Microphone / Speaker
Other Special Feature	Volume control, Pairing
Battery Type	Li-on
Battery Capacity	1300mA, Replaceable *Max. Monitor time • When VOX on - LCD turns off : 6hrs • When VOX off - video always on : 4.2hrs
Battery Time Duration	Min. 4 hours
Weight	215g (0.47 lb)

Design and specifications are subject to change without notice.



SAMSUNG TECHWIN CO., LTD.

6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, SEOUL 463-400 Rep. of KOREA



SAMSUNG TECHWIN