

SLA-3580DN/2810D/550DA/612DN

1/3", 1/2" CS-mount Auto Iris Lens



SLA-3580DN

SLA-2810D

SLA-550DA

SLA-612DN



Key Features

- F1.0 (SLA-3580DN), F1.4 (SLA-2810D/550DA)
F1.6 (SLA-612DN) DC type auto iris
- Vari-focal 3.5 ~ 8mm / 0.14" ~ 0.31" (SLA-3580DN)
2.8 ~ 10mm / 0.11" ~ 0.39" (SLA-2810D)
5 ~ 50mm / 0.2" ~ 1.97" (SLA-550DA)
6 ~ 12mm / 0.24" ~ 0.47" (SLA-612DN)

Technical Specifications

	SLA-3580DN	SLA-2810D	SLA-550DA	SLA-612DN
CCD	1/3"	1/3"	1/3"	1/2"
Resolution	VGA	VGA	VGA	VGA
Focal Length	3.5 ~ 8mm 0.14" ~ 0.31"	2.8 ~ 10mm 0.11" ~ 0.39"	5 ~ 50mm 0.2" ~ 1.97"	6 ~ 12mm 0.24" ~ 0.47"
Max. Aperture Ratio	1 : 1 ~ 360	1 : 1.4 ~ 360	1 : 1.4 ~ 360	1 : 1.6 ~ 300
Max. Image Format	4.8(H) x 3.6(V)	4.8(H) x 3.6(V)	4.8(H) x 3.6(V)	6.4(H) x 4.8(V)
Angle of View	Diagonal	111.2° ~ 44.7°	115.8° ~ 35.3°	65.7° ~ 7.2°
	Horizontal	83.5° ~ 35.6°	93.7° ~ 28.3°	52.7° ~ 5.7°
	Vertical	60.4° ~ 26.6°	70.6° ~ 21.2°	39.6° ~ 4.3°
Operation	Iris	Auto (F1.0 ~ 360)	Auto (F1.4 ~ 360)	Auto (F1.4 ~ 360)
	Focus	Manual	Manual	Manual
	Zoom	Manual	Manual	Manual
Iris Type	DC	DC	DC	DC
Effective Lens	Front	Ø17.5mm Ø0.69"	Ø20.5mm Ø0.81"	Ø37.7mm Ø1.48"
	Rear	Ø8.8mm Ø0.37"	Ø8.8mm Ø0.35"	Ø10mm Ø0.4"
Aperture	Ø8.8mm Ø0.37"	Ø8.8mm Ø0.35"	Ø10mm Ø0.4"	Ø9mm Ø0.35"
Back Focal Length	8.7 ~ 14.7mm 0.34" ~ 0.58"	7.8 ~ 17mm 0.3" ~ 0.67"	7.6 ~ 11.5mm 0.3" ~ 0.45"	7.55 ~ 12.13mm 0.3" ~ 0.48"
Flange Back Length	12.5mm / 0.49"	12.5mm / 0.49"	12.5mm / 0.49"	12.5mm / 0.49"
Mount	CS-mount	CS-mount	CS-mount	CS-mount
Dimensions (WxHxD)	38.6 x 45.3 x 46.0mm (1.52" x 1.78" x 1.81")	40.0 x 46.0 x 57.2mm (1.57" x 1.81" x 2.25")	44.5 x 50.8 x 66.2mm (1.75" x 2" x 2.61")	40.4 x 45.7 x 43.5mm (1.6" x 1.8" x 1.71")
Weight	54.5g (0.12 lb)	65g (0.14 lb)	126g (0.28 lb)	53g (0.12 lb)

Dimensions

Unit : mm (inch)

