

## SCV-5082P

**1/3 CMOS Colour/B&W Camera, 1000L, 12VDC/24VAC**

- 1000 TV Lines
- Privacy function
- Coax Control Interface

**Summary**

The Beyond series offers you a hassle free alternative when updating your analogue (PAL) CCTV system. The 1280H cameras enable you to keep the familiarity and simplicity of analogue surveillance whilst enjoying the outstanding image quality and technically advanced features of 1000TV lines:

Enhanced Wide Dynamic Range for even greater clarity

Unique SSNR IV noise reduction technology

Easy to configure and even easier to operate

These advanced features take you beyond what has previously been possible from analogue solutions. To discover the best in analogue book a demonstration from our sales team or at a partner event.

## Technical Specifications

<b>Image Sensor</b>	1/3" Progressive Scan CMOS, 1.3 Megapixel
<b>Pixels - Total</b>	1312(H) x 1069(V)
<b>Pixels - Effective</b>	1305(H) x 1049(V)
<b>Lens Focal Length</b>	2.8 ~ 10 mm
<b>Lens Drive Type</b>	Auto iris (DC)
<b>Sensitivity Colour</b>	0.037 Lux @ F2.3
<b>Sensitivity B/W</b>	0.01 lux @ F1.2
<b>S/N Ratio</b>	>52dB (AGC off)
<b>Video Outputs</b>	BNC
<b>OSD</b>	Yes, multi language
<b>Camera ID</b>	Off / On
<b>Col/B</b>	On/Off/Auto
<b>BLC Back Light</b>	Off/ User BLC/ HLC
<b>Number of Privacy Zones</b>	24
<b>Digital Noise Reduction (DNR)</b>	SSNR IV (Off/On)
<b>Motion Detection</b>	On/Off
<b>White Balance</b>	Auto, ATW, Indoor, Outdoor, Manual
<b>Digital Zoom</b>	Off/1 ~ 16x
<b>Shutter Speed</b>	1 ~ 1/12.000 sec
<b>Coaxial control</b>	Pelco-C (Coaxitron®)
<b>Operating Temperature</b>	-10°C ~ +55°C
<b>Humidity</b>	less than 90%, non condensing
<b>Protection Rating</b>	IK10, IP66
<b>Supply Voltage</b>	12 Vdc, 24 Vac
<b>Power Consumption (W)</b>	4,5
<b>Weight</b>	0.720 kg - 1.59 lbs

# SCV-5082P

## Dimensions

